




The main body parts are made of aluminum alloy and then shaped by CNC machines. The surface is treated by powder-coating.

The reflector is heat-resistant and anti-glare and will not discolor in long time and reflectance will not decay either.

Simple design with efficient radiator, suitable for different applications.



IP65

LED 15W		cd/Klm	Beam Angle: 23.47°	
1 m	4174 lx		0.42 m	
2 m	1043 lx		0.83 m	
3 m	463.7 lx		1.25 m	
4 m	260.8 lx		1.66 m	
5 m	166.9 lx		2.08 m	
High illuminance			Diameter	

TS903S-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 15W @ DC 36V 400mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 1067 lm
 CRI: 90
 Beam Angle: 24° / 36° / 60°
 Cut Off: 60°
 Control: 0-10V / Dali

IP65

LED 20W		cd/Klm	Beam Angle: 23.8°	
1 m	4972 lx		0.42 m	
2 m	1243 lx		0.84 m	
3 m	552.4 lx		1.26 m	
4 m	310.7 lx		1.69 m	
5 m	198.9 lx		2.11 m	
High illuminance			Diameter	

TS903-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 20W @ DC 36V 530mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 1285 lm
 CRI: 90
 Beam Angle: 24° / 36° / 60°
 Cut Off: 60°
 Control: 0-10V / Dali

