



The main body parts are made of aluminum alloy and then shaped by CNC machines. The surface is treated by powder-coating.

The reflector is heat-resistant and anti-glare and will not discolor in long time and reflectance will not decay either.

Simple design with efficient radiator, suitable for different applications.



Ø 125mm

IP65

LED 25W		Beam Angle: 21.76°	
od/Klm			
1 m	5864 lx	0.38 m	
2 m	1466 lx	0.77 m	
3 m	651.6 lx	1.15 m	
4 m	366.5 lx	1.54 m	
5 m	234.6 lx	1.92 m	
	High illuminance	Diameter	

TS904L-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 25W @ DC 36V 700mA Driver
 Input Voltage: AC 220V/ 50Hz
 Lumens: 1899 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali

IP65

LED 30W		Beam Angle: 21.12°	
od/Klm			
1 m	8251 lx	0.37 m	
2 m	2063 lx	0.75 m	
3 m	916.8 lx	1.12 m	
4 m	515.7 lx	1.49 m	
5 m	330.0 lx	1.86 m	
	High illuminance	Diameter	

TS904M-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 30W @ DC 36V 840mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 2483 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali