



The main body parts are made of aluminum alloy and then shaped by CNC machines. The surface is treated by powder-coating.

The reflector is heat-resistant and anti-glare and will not discolor in long time and reflectance will not decay either.

Simple design with efficient radiator, suitable for different applications.



IP65

LED 25W		cd/Klm	Beam Angle: 22.6°	
60°	1780	1 m	8292 lx	0.40 m
	3400	2 m	2073 lx	0.80 m
	5100	3 m	921.4 lx	1.20 m
	6800	4 m	518.3 lx	1.60 m
30°	8500	5 m	331.7 lx	2.00 m
		High illuminance	Diameter	

## TS903L-LED

Power: LED 25W @ DC 36V 700mA Driver  
 Input Voltage: AC 220V/ 50Hz  
 Lumens: 1957 lm  
 CRI: 90  
 Beam Angle: 24° / 36° / 60°  
 Cut Off: 60°  
 Control: 0-10V / Dali

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

IP65

LED 30W		cd/Klm	Beam Angle: 21.97°	
60°	3000	1 m	10845 lx	0.39 m
	6000	2 m	2711 lx	0.78 m
	9000	3 m	1205 lx	1.16 m
	12000	4 m	677.8 lx	1.55 m
30°	15000	5 m	433.8 lx	1.94 m
		High illuminance	Diameter	

## TS903M-LED

Power: LED 30W @ DC 36V 840mA Driver  
 Input Voltage: AC 220V / 50Hz  
 Lumens: 2525 lm  
 CRI: 90  
 Beam Angle: 24° / 36° / 60°  
 Cut Off: 60°  
 Control: 0-10V / Dali

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

