



The main body parts are made of aluminum alloy and then shaped by CNC machines. The surface is treated by powder-coating.

The reflector is heat-resistant and anti-glare and will not discolor in long time and reflectance will not decay either.

Simple design with efficient radiator, suitable for different applications.



IP65    

LED 15W		cd/Klm	Beam Angle: 24.9°	
60°	1 m	2385 lx	0.44 m	
	2 m	596.3 lx	0.88 m	
	3 m	265.0 lx	1.32 m	
	4 m	149.1 lx	1.77 m	
	5 m	95.41 lx	2.21 m	
30°		High illuminance	Diameter	

TS904S-LED

Power: LED 15W @ DC 36V 400mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 942 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

IP65    

LED 20W		cd/Klm	Beam Angle: 33.54°	
60°	1 m	2782 lx	0.60 m	
	2 m	695.4 lx	1.21 m	
	3 m	309.1 lx	1.81 m	
	4 m	173.9 lx	2.41 m	
	5 m	111.3 lx	3.01 m	
30°		High illuminance	Diameter	

TS904-LED

Power: LED 20W @ DC 36V 530mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 1234 lm
 CRI: 90
 Beam Angle: 20° / 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

