



The main body parts are made of aluminum alloy and then shaped by CNC machines. The surface is treated by powder-coating.

The reflector is heat-resistant and anti-glare and will not discolor in long time and reflectance will not decay either.

Simple design with efficient radiator, suitable for different applications.



IP65

LED 30W		Beam Angle: 30.2°	
60°	3000	1 m	8251 lx
60°	3000	2 m	2063 lx
60°	3000	3 m	916.8 lx
60°	3000	4 m	515.7 lx
60°	3000	5 m	330.0 lx
30°	12000		
30°	15000		
High illuminance		Diameter	

TS902S-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 30W @ DC 36V 840mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 2492 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali

IP65

LED 35W		Beam Angle: 28.8°	
60°	4000	1 m	4504 lx
60°	3000	2 m	1126 lx
60°	3000	3 m	500.5 lx
60°	3000	4 m	281.5 lx
60°	3000	5 m	180.2 lx
30°	16000		
30°	20000		
High illuminance		Diameter	

TS902-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 35W @ DC 36V 900mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 3075 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali

IP65

LED 40W		Beam Angle: 31.5°	
60°	4000	1 m	7364 lx
60°	3400	2 m	1841 lx
60°	3400	3 m	818.2 lx
60°	3400	4 m	460.2 lx
60°	3400	5 m	294.5 lx
30°	6000		
30°	8500		
High illuminance		Diameter	

TS902L-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 40W @ DC 36V 1050mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 3373 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali

IP65

LED 50W		Beam Angle: 27.2°	
60°	4000	1 m	14678 lx
60°	3000	2 m	3669 lx
60°	3000	3 m	1631 lx
60°	3000	4 m	917.4 lx
60°	3000	5 m	587.1 lx
30°	16000		
30°	20000		
High illuminance		Diameter	

TS902M-LED

CCT: 2700 / 3000 / 3500 / 4000 / 5000 / 6500 K

Power: LED 50W @ DC 36V 1200mA Driver
 Input Voltage: AC 220V / 50Hz
 Lumens: 3694 lm
 CRI: 90
 Beam Angle: 30° / 45° / 60°
 Cut Off: 55°
 Control: 0-10V / Dali